



SUPER-TEK

Perfect Seal Caulk

Perfect Seal Caulk is an easy to use acrylic caulk formulated specifically to match all of Super-Tek's grout colors. Perfect for creating a professional designer look. For use around tubs, showers, counter tops, backsplashes, thresholds and windows. Non-Sag formula allows for use on vertical installations

- **Bonds to Most Surfaces**
- **Tough and Flexible**
- **Indoor or Outdoor use**
- **Moisture, Mildew and UV Resistant**

Installation

Approved Substrates

Properly prepared ceramic tile, stone, brick, concrete, wood, plaster, metal, glass, fiberglass, and high pressure laminates.

PLEASE NOTE: This product contains colorants that may stain some porous materials. Mask or protect these areas to protect from staining. Test an inconspicuous area first.

Application

- 1) Surfaces must be clean and free of dust, dirt, oil and other foreign substances. Remove old caulk or sealants.
- 2) Cut tip to desired bead thickness.
- 3) Apply caulk bead by drawing tube towards you. Maintain pressure while applying.
- 4) Shape caulking within 20 minutes of application. Use wet finger or smooth wet sponge.

Curing

Jobsite temperature must remain between 45°F and 95°F for a minimum of 72 hours after installation.

Clean Up

Excess may be cleaned up with warm soapy water when fresh. Cured material can be cut or scraped away with a razor blade.

LIMITATIONS: Do not use at temperatures below 40°F. Not for use under water.

Packaging

10.3 oz. Tubes with 10 tubes per case.

Shelf Life: One year when stored in original packaging in a dry, ventilated place. Exposure to moisture will shorten the shelf life.

Technical Assistance

Monday through Friday
8:00 AM to 4:30 PM EST
T 718-278-7900 ext. 111

By e-mail: info@super-tek.com

Or our website: www.super-tek.com

WARNING! EYE AND SKIN IRRITANT. Avoid contact with eyes, skin and clothing. Wash thoroughly after handling. In case of eye contact, immediately flush with plenty of water for at least 15 minutes, consult physician immediately. For skin contact, wash affected area with soap and water. For additional information, see Safety Data Sheet (SDS) for this product on our website.

KEEP OUT OF THE REACH OF CHILDREN!

NOTICE AND WARRANTY DISCLAIMER: The MANUFACTURER has provided these Instructions/ Recommendations [I/R] to assist the USER in the application of this product. These I/Rs are not warranted to be comprehensive, complete, thorough or conclusive as regards any specific installation. Before using, USER shall determine the suitability of the product for its intended use and USER alone assumes all risks and liability whatsoever in connection therewith. The liability of the SELLER and the MANUFACTURER, whether express or implied, whether in contract or in tort, arising out of warranties, representations, instructions or defects from any cause shall be limited exclusively to replacing the product, provided the same is proved defective, or refunding the purchase price upon return of the unused product. In no event will SELLER or MANUFACTURER be liable for consequential damages, including but not limited to, loss of materials, costs of labor, loss of profits, costs of replacement goods, or other commercial loss. The USER accepts the product AS IS, and without warranties expressed or implied. Any claims shall be deemed waived unless made in writing to MANUFACTURER within ten (10) days from date it was, or reasonably should have been, discovered.

**High
performance
ceramic tile,
stone and
marble
installation
products for the
professional
installer**

STP

REV: B, 12/5/2016

Super-Tek Products, Inc. • www.super-tek.com

25-44 Borough Place • Woodside, NY 11377 • T 718-278-7900 • F 718-204-6013

© 2016 Super-Tek Products, Inc.

